



Magic Monkey in Maintenance

MM225

Magic Monkey | Granules | Maintenance


Absorbency: 52 Litres | 11.5 US Gallons of oil**
41 Litres | 6 US Gallons of water**

Base Fibre: Mineral



| Product Code | Colour | Format | Size cm (inches) | Recycled Content | Units/Case | Weight/Case*** | LTl/Pallet | FTL/Pallet |
|--------------------|-----------|-------------|---------------------------|------------------|------------|------------------|------------|------------|
| Maintenance | | | | | | | | |
| MM225 | Off white | Maintenance | 60 cm x 66 cm (24" x 26") | 100%* | 1 Bag | 11.3 kg (25 lbs) | 70 | 70 |

Magic Monkey Granules



This product is in a Maintenance format



This product features 100% recycled content

This lightweight, dry, granular sorbent is safe for people, plants, animals, and food processing facilities. The granular sorbent is sprinkled on to the spill which then turns into a solid. The spill can then be easily swept away with a broom.

Key features

- Absorbs liquids of any viscosity and leaves surfaces clean and dry
- Lightweight even when saturated, making it less costly to dispose of than heavier granular sorbents
- Safe for people, plants, animals and food processing facilities or surfaces including concrete, tile and asphalt

Application

Effective on most types of spills including oils, fuels, chemicals, paint, antifreeze, bases, bodily fluids, non-hydrofluoric acids, and many others.

Notes

- DO NOT USE WITH HYDROFLUORIC ACID
- Ensure that disposal of these sorbents complies with all local, state and federal regulations.

See this product in action on our website



* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

| Related Regulations | Description |
|---------------------------|---|
| 29CFR 1910.22(a)(2) | "The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition." |
| 29CFR 1910.120(j)(1)(vii) | "... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur." |