



227 Litre (60 Gallon) Dash Bin Chemical Spill Kit

DASH-Y60

Spill kit | 113 Litre | Chemical | Dash bin

Absorbency: 227 Litres | 60 US Gallons**

Base Fibre: Polypropylene




Product Code	Colour	Format	Size cm (inches)	Recycled Content	Units/Case	Weight/Case	LTL/Pallet	FTL/Pallet
DASH-Y60	Yellow	Spill Kit	N/A	50%*	1	16 kg (35 lbs)	N/A	N/A

227 Litre (60 US Gallon) Dash Bin

A highly portable wheeled bin with a hinged lid that is ideal for locations where a large quantity of sorbents need to be taken to the site of a spill at a moments notice. The wheels are made from tough rubber and cannot puncture.


This spill kits feature a combination of pads and socks that will contain and recover a 227 litre spill of hazardous oil-based and

Spill kit's contents include:



100 x Pads
size 38 cm x 46 cm (15" x 18")

The pads in this spill kit are medium weight sonic bonded meltblown polypropylene Chemical. They feature excellent wicking properties and sonic bond points that prevent stray fibres from becoming detached.



15 x Socks
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable stitched seam. The core is a next generation absorbent that will recover aggressive and unknown spills. Durable plastic clips seal the sock at both ends.



6 x Pillows
size 23 cm x 38 cm

These pillows feature a spun-bond outer surface with a super absorbent flake core. This next generation absorbent will absorb and hold large quantities of aggressive, hazardous or unknown fluids.



10 x Waste Bags

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

2 pairs of gloves

Waterproof gloves help to ensure safe handling of spilled substance.

2 pairs of goggles

All-in one clear goggles provide eye protection from splashes.

1 guide book

An informative booklet that advises on spill recovery.

water-based fluid as well as the essential equipment needed to handle the clean up process. Please note extra caution should be taken when dealing with hazardous or unknown spill types.

Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.