



# 20 Litre (5 gallon) Portable Bucket Maintenance Spill Kit

SK-U05P

Spill kit | 20 Litre | Maintenance | Plastic bucket

**Absorbency:** 20 Litres | 5 US Gallons\*\*

**Base Fibre:** Cellulose



Product Code	Colour	Format	Size cm(inches)	Recycled Content	Units/Case	Weight/Case	LTL/Pallet	FTL/Pallet
SK-U05P	Grey	Spill Kit	N/A	70%*	1	3.6 kg (8 lbs)	40	40

## 20 Litre (5 US Gallon) Bucket


The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A clip top lid and a metal handle make for easy portability and quick deployment. Great for indoor or outdoor use and also to add extra support to larger spill kits.

This spill kits feature a combination of pads and socks that will contain and recover a 20 litre spill of oil-based and water-based fluid as well as the basic equipment needed to handle the clean up process.

### Notes

- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

### Spill kit's contents include:



**10 x Pads**  
size 40 cm x 46 cm (16" x 18")

The pads in this spill kit are medium weight Coldform2™ and feature recycled and renewable sourced natural fibres. A spun-bond lamination is added for extra strength. These pads will recover both oil and water-based fluids.



**3 x Socks**  
size 8 cm x 1.2 m (3" x 4')

These socks feature a spun-bond outer sleeve with a durable heat sealed seam. This tube is then filled with a next generation super absorbent flake core and sealed with a durable metal clip.



**1 x Waste Bag**

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

**1 pair of gloves**

Waterproof gloves help to ensure safe handling of spilled substance.

**1 pair of goggles**

All-in one clear goggles provide eye protection from splashes.

\* Basis weights and recycled content are ± 5%

\*\* Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

\*\*\* Weight per case ± 0.5 kg/lbs.

### Compliance

Related Regulations	Description
29 CFR 1910.120(j)(1)(vii)	...suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.120(j)(1)(vii)	U.S. Department of Transportation specified salvage drums or containers and suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur.
29 CFR 1910.22(a)(2)	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition.
40 CFR 263.31	Transporters "must clean up any hazardous waste discharge that occurs during transportation.