

Collapsible Mini Berms

Collapsible Mini Berms | Secondary Containment

PVC Collapsible Mini Berms

| Product Code | Width | Length | Height | Fabric Weights |
|--------------|------------|-------------------|-------------|----------------|
| MBY244 | 610 mm (2 | 4") 610 mm (24") | 111 mm (4") | 22oz |
| MBY364 | 914 mm (3 | 6") 914 mm (36") | 111 mm (4") | 22oz |
| MBY484 | 1219 mm (4 | 8") 1219 mm (48") | 111 mm (4") | 22oz |
| MBY246 | 610 mm (2 | 4") 610mm (24") | 150mm (6") | 22oz |
| MBY366 | 914 mm (3 | 6") 914mm (36") | 150mm (6") | 22oz |
| MBY486 | 1219 mm (4 | 8") 1219mm (48") | 150mm (6") | 22oz |



1000年500

Also available in 28oz PVC and Arctic-Shield Fabric (Fire resistant and certified by Intertek)

Special Order Custom Sizes



The Mini-Berm is an ultra-lightweight and convenient spill tray for clean-up operations and spill prevention during fuel and chemical transfer. Mini-Berm trays are easily placed under valves, fittings, vehicles or machinery.

Totally reusable and compact, the Mini-Berm withstands most liquids, is designed to take standard-sized sorbent pads and meets EPA regulation 40CFR112.7

Constructed of durable fabric that is resistant to chemicals, fuels, oils, and acids.

- · Compact and lightweight for storage and easy transport
- Easily cleaned and maintained
- · Designed to take standard size sorbent pads.
- Appropriate for containment of waste water, petroleum products and various other chemicals

Chemshield Collapsible Mini Berms

| Product Code | Width | Length | Height | Fabric Weights |
|--------------|---------------|---------------|-------------|----------------|
| MBB244 | 610 mm (24") | 610 mm (24") | 111 mm (4") | 30oz |
| MBB364 | 914 mm (36") | 914 mm (36") | 111 mm (4") | 30oz |
| MBB484 | 1219 mm (48") | 1219 mm (48") | 111 mm (4") | 30oz |
| MBB246 | 610 mm (24") | 610mm (24") | 150mm (6") | 30oz |
| MBB366 | 914 mm (36") | 914mm (36") | 150mm (6") | 30oz |
| MBB486 | 1219 mm (48") | 1219mm (48") | 150mm (6") | 30oz |



Related Regulations Description

29CFR 1910.22(a)(2) "The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition." 29CFR 1910.120(j)(1)(vii) "... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."