



Drain Seal®

UT2130



Drain Seal | Secondary Containment

| Product Code | Dimensions cm (inches) | Weight kg (lbs) | LTL/Pallet | FTL/Pallet |
|--------------|------------------------------------|-----------------|------------|------------|
| UT2130 | 91.5 x 91.5 x 1 (36" x 36" x 3/8") | 9 kg (20.0 lbs) | - | - |

- Reinforcing mesh is "sandwiched" between layers of polyurethane— increases durability and resistance to tearing.
- Unique, urethane construction allows the pad to deform and seal off most drains — temporarily "seals" to any smooth surface.
- A valuable addition to any emergency response plan, spill kit, SPCC, or storm water management program.
- Unlike some alternative products, BOTH sides will quickly seal drains — there is no specified "top" or "bottom."

Installation:

Easily installed in most drains. Simply lay the seal mat over the drain that requires covering.

Note: Not intended for long-term outdoor use (more than two [2] hours), as UV exposure and/or heat for extended periods can degrade the product. For applications where extended use may be required, the Ultra-Drain Seal Plus should be considered.



* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

| Related Regulations | Description |
|---------------------------|---|
| 29CFR 1910.22(a)(2) | "The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition." |
| 29CFR 1910.120(j)(1)(vii) | "... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur." |