



2 Rag Rugs Rolls in Maintenance

1RR18150

Rag Rug | Maintenance

Absorbency: 110 Litres | 29 US Gallons of oil**


87 Litres | 23 US Gallons of water**

Base Fibre: Polypropylene



Product Code	Colour	Format	Size cm(inches)	Recycled Content	Units/Case	Weight/Case***	LTL/Pallet	FTL/Pallet
Maintenance								
1RR18150	Mixed	Maintenance	46 cm x 46 m (18" x 150')	100%*	2/ bale	22.6 kg (50 lbs)	12	12

Rag rug



This product is in a Maintenance format



This product features recycled and natural fibres

Constructed from a single layer of 100% recycled natural and synthetic fibres, this roll will absorb both oil- and water-based spills.

Key features

- One of the most excellent value absorbent products anywhere.
- Needle-punched and heat-set single layer of recycled fibres make rugs sturdy, long lasting and extremely absorbent.

Application

Use it in strips in narrow spaces or simply lay out long rolls alongside machines, on walkways, or wherever you need heavy-duty, absorbent rugs. Use rolls to cover long areas quickly.

Notes

- Fire retardant as per ASTM 726
- Avoid high-heat applications
- Ensure that disposal of these sorbents complies with all regulations.

* Basis weights and recycled content are ± 5%

** Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data.

*** Weight per case ± 0.5 kg/lbs.

Compliance

Related Regulations	Description
29CFR 1910.22(a)(2)	"The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition."
29CFR 1910.120(j)(1)(vii)	"... suitable quantities of proper absorbents shall be kept available and used in areas where spills, leaks or ruptures may occur."